


Perdite di carico - Loss of pressure - Pertes de charge - Druckverlust - Pérdida de carga - Perdas de carga - Drukweerstand



N° GIRI DETENTORE PARTENDO DA TUTTO CHIUSO NO. LOCKSHIELD TURNS STARTING FROM FULLY CLOSED	Kv
0,25	0,14
1	0,17
1,25	0,24
1,5	0,35
2	0,53
2,5	0,58
3	0,73
3,5	0,85
F.O.	0,91

⚠ Safety Warning. Installation, commissioning and periodical maintenance of the product must be carried out by qualified operators in compliance with national regulations and/or local standards. A qualified installer must take all required measures, including use of Individual Protection Devices, for his and others' safety. An improper installation may damage people, animals or objects towards which Giacomini S.p.A. may not be held liable.

♻ Package Disposal. Carton boxes: paper recycling. Plastic bags and bubble wrap: plastic recycling.

ℹ Additional information. For more information, go to giacomini.com or contact our technical assistance service. This document provides only general indications. Giacomini S.p.A. may change at any time, without notice and for technical or commercial reasons, the items included herewith. The information included in this technical sheet do not exempt the user from strictly complying with the rules and good practice standards in force.

♻ Product Disposal. Do not dispose of product as municipal waste at the end of its life cycle. Dispose of product at a special recycling platform managed by local authorities or at retailers providing this type of service.

R53MM R53MT

Istruzioni/Instruction
047U23378 03/2020



(IT)

- Collettore modulare ad aggancio rapido con misuratore di portata
- Campo di temperatura: 5-110 °C
- Pressione massima di esercizio: 10 bar
- Utilizzabile per acqua usi riscaldamento e raffrescamento

(EN)

- Modular manifold with quick-connection with flow meter
- Temperature range: 5-110 °C
- Max. working pressure: 10 bar
- Suitable for water for heating and cooling

(FR)

- Collecteur modulaire avec débitmètre
- Température de service maximum: 5-110 °C
- Pression de service maximum: 10 bar
- Utilisable pour l' eau, usage chauffage et rafraîchissement

(DE)

- Modulverteiler mit Bajonett Schnellkupplung und Durchflussmesser
- Max. Betriebstemperatur: 5-110 °C
- Max. Betriebsdruck: 10 bar
- Anwendung für Wasser in Heizungs-, Klimainstallationen

(ES)

- Colector modular a bayoneta con medidor de caudal
- Temperatura máxima de trabajo: 5-110 °C
- Presión máxima de trabajo: 10 bar
- Utilizable para agua de calefacción y climatización.

(PT)

- Colector modular de encaixe rápido com caudalímetro
- Temperatura máxima de trabalho: 5-110 °C
- Pressão máxima de trabalho: 10 Bar
- Indicado para instalações de aquecimento e climatização

(NL)

- Modulaire verdeler met snelkoppeling, met inregelventiel en debietmeter
- Max.temperatuur: 5-110 °C
- Max.werkdruk: 10 bar
- Voor gebruik met water in verwarmings- of koelingsinstallaties

R53MM R53MT

Istruzioni/Instruction
047U23378 03/2020



(IT)

- Collettore modulare ad aggancio rapido con misuratore di portata
- Campo di temperatura: 5-110 °C
- Pressione massima di esercizio: 10 bar
- Utilizzabile per acqua usi riscaldamento e raffrescamento

(EN)

- Modular manifold with quick-connection with flow meter
- Temperature range: 5-110 °C
- Max. working pressure: 10 bar
- Suitable for water for heating and cooling

(FR)

- Collecteur modulaire avec débitmètre
- Température de service maximum: 5-110 °C
- Pression de service maximum: 10 bar
- Utilisable pour l' eau, usage chauffage et rafraîchissement

(DE)

- Modulverteiler mit Bajonett Schnellkupplung und Durchflussmesser
- Max. Betriebstemperatur: 5-110 °C
- Max. Betriebsdruck: 10 bar
- Anwendung für Wasser in Heizungs-, Klimainstallationen

(ES)

- Colector modular a bayoneta con medidor de caudal
- Temperatura máxima de trabajo: 5-110 °C
- Presión máxima de trabajo: 10 bar
- Utilizable para agua de calefacción y climatización.


(PT)

- Colector modular de encaixe rápido com caudalímetro
- Temperatura máxima de trabalho: 5-110 °C
- Pressão máxima de trabalho: 10 Bar
- Indicado para instalações de aquecimento e climatização

(NL)

- Modulaire verdeler met snelkoppeling, met inregelventiel en debietmeter
- Max.temperatuur: 5-110 °C
- Max.werkdruk: 10 bar
- Voor gebruik met water in verwarmings- of koelingsinstallaties

Perdite di carico - Loss of pressure - Pertes de charge - Druckverlust - Pérdida de carga - Perdas de carga - Drukweerstand



N° GIRI DETENTORE PARTENDO DA TUTTO CHIUSO NO. LOCKSHIELD TURNS STARTING FROM FULLY CLOSED	Kv
0,25	0,14
1	0,17
1,25	0,24
1,5	0,35
2	0,53
2,5	0,58
3	0,73
3,5	0,85
F.O.	0,91


⚠ Safety Warning. Installation, commissioning and periodical maintenance of the product must be carried out by qualified operators in compliance with national regulations and/or local standards. A qualified installer must take all required measures, including use of Individual Protection Devices, for his and others' safety. An improper installation may damage people, animals or objects towards which Giacomini S.p.A. may not be held liable.

♻ Package Disposal. Carton boxes: paper recycling. Plastic bags and bubble wrap: plastic recycling.

ℹ Additional information. For more information, go to giacomini.com or contact our technical assistance service. This document provides only general indications. Giacomini S.p.A. may change at any time, without notice and for technical or commercial reasons, the items included herewith. The information included in this technical sheet do not exempt the user from strictly complying with the rules and good practice standards in force.

♻ Product Disposal. Do not dispose of product as municipal waste at the end of its life cycle. Dispose of product at a special recycling platform managed by local authorities or at retailers providing this type of service.

Perdite di carico - Loss of pressure - Pertes de charge - Druckverlust - Pérdida de carga - Perdas de carga - Drukweerstand



N° GIRI DETENTORE PARTENDO DA TUTTO CHIUSO NO. LOCKSHIELD TURNS STARTING FROM FULLY CLOSED	Kv
0,25	0,14
1	0,17
1,25	0,24
1,5	0,35
2	0,53
2,5	0,58
3	0,73
3,5	0,85
F.O.	0,91

⚠ Safety Warning. Installation, commissioning and periodical maintenance of the product must be carried out by qualified operators in compliance with national regulations and/or local standards. A qualified installer must take all required measures, including use of Individual Protection Devices, for his and others' safety. An improper installation may damage people, animals or objects towards which Giacomini S.p.A. may not be held liable.

♻ Package Disposal. Carton boxes: paper recycling. Plastic bags and bubble wrap: plastic recycling.

ℹ Additional information. For more information, go to giacomini.com or contact our technical assistance service. This document provides only general indications. Giacomini S.p.A. may change at any time, without notice and for technical or commercial reasons, the items included herewith. The information included in this technical sheet do not exempt the user from strictly complying with the rules and good practice standards in force.

♻ Product Disposal. Do not dispose of product as municipal waste at the end of its life cycle. Dispose of product at a special recycling platform managed by local authorities or at retailers providing this type of service.

R53MM R53MT

Istruzioni/Instruction
047U23378 03/2020



(IT)

- Collettore modulare ad aggancio rapido con misuratore di portata
- Campo di temperatura: 5-110 °C
- Pressione massima di esercizio: 10 bar
- Utilizzabile per acqua usi riscaldamento e raffrescamento

(EN)

- Modular manifold with quick-connection with flow meter
- Temperature range: 5-110 °C
- Max. working pressure: 10 bar
- Suitable for water for heating and cooling

(FR)

- Collecteur modulaire avec débitmètre
- Température de service maximum: 5-110 °C
- Pression de service maximum: 10 bar
- Utilisable pour l' eau, usage chauffage et rafraîchissement

(DE)

- Modulverteiler mit Bajonett Schnellkupplung und Durchflussmesser
- Max. Betriebstemperatur: 5-110 °C
- Max. Betriebsdruck: 10 bar
- Anwendung für Wasser in Heizungs-, Klimainstallationen

(ES)

- Colector modular a bayoneta con medidor de caudal
- Temperatura máxima de trabajo: 5-110 °C
- Presión máxima de trabajo: 10 bar
- Utilizable para agua de calefacción y climatización.

(PT)

- Colector modular de encaixe rápido com caudalímetro
- Temperatura máxima de trabalho: 5-110 °C
- Pressão máxima de trabalho: 10 Bar
- Indicado para instalações de aquecimento e climatização

(NL)

- Modulaire verdeler met snelkoppeling, met inregelventiel en debietmeter
- Max.temperatuur: 5-110 °C
- Max.werkdruk: 10 bar
- Voor gebruik met water in verwarmings- of koelingsinstallaties

R53MM R53MT

Istruzioni/Instruction
047U23378 03/2020



(IT)

- Collettore modulare ad aggancio rapido con misuratore di portata
- Campo di temperatura: 5-110 °C
- Pressione massima di esercizio: 10 bar
- Utilizzabile per acqua usi riscaldamento e raffrescamento

(EN)

- Modular manifold with quick-connection with flow meter
- Temperature range: 5-110 °C
- Max. working pressure: 10 bar
- Suitable for water for heating and cooling

(FR)

- Collecteur modulaire avec débitmètre
- Température de service maximum: 5-110 °C
- Pression de service maximum: 10 bar
- Utilisable pour l' eau, usage chauffage et rafraîchissement

(DE)

- Modulverteiler mit Bajonett Schnellkupplung und Durchflussmesser
- Max. Betriebstemperatur: 5-110 °C
- Max. Betriebsdruck: 10 bar
- Anwendung für Wasser in Heizungs-, Klimainstallationen

(ES)

- Colector modular a bayoneta con medidor de caudal
- Temperatura máxima de trabajo: 5-110 °C
- Presión máxima de trabajo: 10 bar
- Utilizable para agua de calefacción y climatización.


(PT)

- Colector modular de encaixe rápido com caudalímetro
- Temperatura máxima de trabalho: 5-110 °C
- Pressão máxima de trabalho: 10 Bar
- Indicado para instalações de aquecimento e climatização

(NL)

- Modulaire verdeler met snelkoppeling, met inregelventiel en debietmeter
- Max.temperatuur: 5-110 °C
- Max.werkdruk: 10 bar
- Voor gebruik met water in verwarmings- of koelingsinstallaties

Perdite di carico - Loss of pressure - Pertes de charge - Druckverlust - Pérdida de carga - Perdas de carga - Drukweerstand



N° GIRI DETENTORE PARTENDO DA TUTTO CHIUSO NO. LOCKSHIELD TURNS STARTING FROM FULLY CLOSED	Kv
0,25	0,14
1	0,17
1,25	0,24
1,5	0,35
2	0,53
2,5	0,58
3	0,73
3,5	0,85
F.O.	0,91

⚠ Safety Warning. Installation, commissioning and periodical maintenance of the product must be carried out by qualified operators in compliance with national regulations and/or local standards. A qualified installer must take all required measures, including use of Individual Protection Devices, for his and others' safety. An improper installation may damage people, animals or objects towards which Giacomini S.p.A. may not be held liable.

♻ Package Disposal. Carton boxes: paper recycling. Plastic bags and bubble wrap: plastic recycling.

ℹ Additional information. For more information, go to giacomini.com or contact our technical assistance service. This document provides only general indications. Giacomini S.p.A. may change at any time, without notice and for technical or commercial reasons, the items included herewith. The information included in this technical sheet do not exempt the user from strictly complying with the rules and good practice standards in force.

♻ Product Disposal. Do not dispose of product as municipal waste at the end of its life cycle. Dispose of product at a special recycling platform managed by local authorities or at retailers providing this type of service.