Valve for water for heating/cooling systems and not dangerous gas
Full port - R789 series







Description

Angle ball valve, with female-tail piece male threaded connections. Full port.

Versions and product codes

Product code	Connections	Finishing	Handle type	Handle color	
R789X003	G 1/2"F x G 1/2"M	Chrome plated brass	T-handle	Red	
R789X005	G 3/4"F x G 3/4"M	Chrome plated brass	T-handle	Red	
R789X007	G 1"F x G 1"M	Chrome plated brass	T-handle	Red	

Technical data

Main features and materials


- Suitable for water for heating/cooling systems and not dangerous gas
- Full port
- Valve made of UNI EN 12165 CW617N chrome plated brass
- Stem with double O-Ring
- Nut with anti-corrosion coating, with guarantee seal and hologram
- · Aluminium T-handle, red painted

Field of applications

- Temperature range: -20÷120 °C (-20 °C with 50 % glycol solutions)
- Max. working pressure at 20 °C with water and not dangerous gas: 1,6 MPa (16 bar)

Dimensions and Kv

Product code	DN	A [mm]	l [mm]	B [mm]	J [mm]	C [mm]	H [mm]	H'[mm]	Kv
R789X003	15	79	18	71	33	63	wr.26	wr.30	4,8
R789X005	20	89	21	82	39	73	wr.32	wr.38	8,0
R789X007	25	100	25	94	46	73	wr.41	wr.46	21,3



Product specifications

R789

Angle ball valve, with female-tail piece male threaded connections.. Suitable for water for heating/cooling systems and not dangerous gas. Valve made of UNI EN 12165 CW617N chrome plated brass. Full port. Aluminium T-handle, red painted. Stem with double O-Ring. Nut with anti-corrosion coating, with guarantee seal and hologram. Temperature range: $-20 \div 120$ °C (-20 °C with 50 % glycol solutions). Max. working pressure at 20 °C with water and not dangerous gas: 1,6 MPa (16 bar).